

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
8 April 2004 (08.04.2004)

PCT

(10) International Publication Number  
**WO 2004/029569 A1**

(51) International Patent Classification<sup>7</sup>: **G01L 3/10**

(74) Agent: **THOMAS, Kurig; Becker, Kurig, Straus, Bavariastrasse 7, 80336 München (DE).**

(21) International Application Number:  
PCT/EP2003/010634

(22) International Filing Date:  
24 September 2003 (24.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
0222296.6 25 September 2002 (25.09.2002) GB

(71) Applicant (for all designated States except US): **FAST TECHNOLOGY AG. [DE/DE]; Otto-Hahn-Strasse 24, 85521 Ottobrunn (DE).**

(72) Inventor; and


(75) Inventor/Applicant (for US only): **MAY, Lutz, Axel [DE/DE]; Wolfratshauser Strasse 23a, 82538 Gelting (DE).**

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: **TORQUE SIGNAL TRANSMISSION**



(57) Abstract: The present invention relates to a torque transducer with a shaft subject to torque about a longitudinal axis. It also relates to a transducer element integral with or carried by the shaft and remanently magnetised to emanate a component of magnetic field that is dependent on torque applied about said axis. A sensor coil is disposed about said element to generate a voltage/current in response to changes in said component. A load is connected to said sensor coil to enable a current circulate in the sensor and a receiver unit remote from said coil and responsive to a field emanated by said sensor coil to generate a torque-dependent signal.

WO 2004/029569 A1



**Published:**

- / with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*